



Tantalean & Associates

CONSULTING ENGINEERS

10071 Shier Way
San Diego, CA. 92129
(619) 538-4737

97-020

DOUBLE WALL STEEL TRENCH SHIELD CERTIFICATION

The following steel shield for trenches was designed in compliance with Federal Register Vol. 54, No. 209, Part 1926, Subpart P, and accepted engineering practice. It must be used in a manner consistent with regulations outlined in subpart P, and local regulations. This rating is not valid if the trench shield shows excessive wear, is permanently damaged, is not maintained properly or repaired properly, this certification is not valid if the steel trench shield is modified in any manner by attaching, welding or resting any other shields or plates to extend the specified height, length, width or clearance call out below. Stacking of steel trench shield is permitted. Shields can be stacked in normal position or in the inverted position with knife edge up.

SPECIFICATIONS

Trench Shield Height	8 ft.
Trench Shield Length	20 ft.
Trench Shield Wall Thickness	4 in.
Trench Shield Capacity	1423 psf
Manufacturer	Safe-T-Shore

THEORETICAL DEPTH

Soil Type	With 72 psf Surcharge	Without Surcharge
Type A	54.1 ft.	56.9 ft.
Type B	30.0 ft.	31.6 ft.
Type C-60	22.5 ft.	23.7 ft.
Type C	16.9 ft.	17.8 ft.

