



Manufacturers and distributors of trench shoring and shielding equipment.

CERTIFICATION SHEET

A COPY OF THIS SHEET MUST ACCOMPANY
EACH CORRESPONDING ARCH AT EVERY JOB SITE

HIGH CLEARANCE ARCH

SERIAL NUMBER: 14574

- THE ARCH SHALL NOT BE USED IN SOIL CONDITIONS OR DEPTH THAT WOULD EXCEED THE MAXIMUM P.S.F. RATINGS SHOWN ON THE BACKSIDE OF THIS CHART.
- THE RATINGS SHOWN ASSUME A SHIELD CAPACITY EQUAL TO OR GREATER THAN THE P.S.F. RATINGS SHOWN ON THIS CHART. IF THE SHIELD CAPACITY IS LESS THAN THE CORRELATING P.S.F. RATING ON THE CHART, THE P.S.F. RATING OF THE SHIELD MUST NOT BE EXCEEDED.
- ALWAYS COMPARE THE MAXIMUM SHIELD CAPACITY TO THE MAXIMUM ARCH CAPACITY USING THE SAME SIZE SHIELD. DO NOT EXCEED THE LOWER OF THE TWO P.S.F. RATINGS.
- TOTAL WIDTH OF THE ARCH SHALL NOT EXCEED 20 FEET WITHOUT WRITTEN APPROVAL FROM **PRO-TEC EQUIPMENT, INC.**
- CONTACT **PRO-TEC EQUIPMENT, INC.** PRIOR TO USING THIS PRODUCT WITH SHIELDS PRODUCED BY ANOTHER MANUFACTURER.
- CONTACT **PRO-TEC EQUIPMENT, INC.** FOR INSTRUCTIONS ON SHIELD MODIFICATIONS REQUIRED TO ALLOW USE OF THE ARCH.
- ALWAYS USE FACTORY SUPPLIED NUTS, BOLTS AND PINS FOR CONNECTING HARDWARE.
- PRO-TEC TRENCH SHIELDS ARE TO BE USED IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL LAWS. REFER TO OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA) RULES AND REGULATIONS VOL. 54, NO.209, 10/31/89, PART 1926, SUBPART P.

Phone (517) 541-0303 • 1-800-292-1225 • Fax (517) 541-0329

Mailing Address: P.O. Box 130 • Charlotte, MI 48813 • Shipping Address: 1298 Lipsey Drive • Charlotte, MI 48813